

Hiroaki KYOUGOKU et al., S.N. 10/531,755
Page 2

Dkt. 2271/74286

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) A semiconductor laser driving device which performs a driving control of a semiconductor laser to control current supplied to the laser so that a desired amount of emission light is obtained, said semiconductor laser driving device comprising:

a first current generating unit generating a first current that is below an oscillation threshold current of the laser, and outputting the first current to the laser invariably;

a second current generating unit generating a second current that is needed for light emission of the laser responsive to an input signal, ~~and outputting the second current to the laser;~~

a third current generating unit generating a third current that controls the laser such that a detected amount of emission light from the laser accords with a given value, and outputting the third current to the laser;

an auxiliary current control unit causing the second current generating unit to generate a predetermined auxiliary current, the second current generating unit outputting a sum of the second current and ~~output~~ the auxiliary current to the laser; and

an initialization unit performing an initialization operation to detect luminescence characteristics of the laser, and outputting a signal, indicating a value of the second current derived from the detected luminescence characteristics, to the second current generating unit,

wherein the third current generating unit controls the third current so that an amount of light outputted by the laser which receives a sum of the first current, the second current, the third

Hiroaki KYOUGOKU et al., S.N. 10/531,755

Dkt. 2271/74286

Page 3

current and the auxiliary current, accords with a predetermined amount.

2. (original) The semiconductor laser driving device of claim 1 wherein the initialization unit performs the initialization operation to detect not only first luminescence characteristics of the laser at a normal temperature but also second luminescence characteristics of the laser at a predetermined high temperature when a same amount of light is outputted by the laser for the two temperatures, and

wherein the auxiliary current control unit causes the second current generating unit to generate the auxiliary current so that the generated auxiliary current is larger than a difference between a value of the second current derived from the first luminescence characteristics and a value of the second current derived from the second luminescence characteristics.

3. (original) The semiconductor laser driving device of claim 1 wherein the second current generating unit comprises a current-output type DAC which generates a predetermined reference current and outputs a current based on the reference current according to a received digital signal, and the auxiliary current control unit causes the second current generating unit to add the auxiliary current to the reference current of the DAC.

4. (original) The semiconductor laser driving device of claim 1 wherein the auxiliary current control unit comprises a current-output type DAC.

5. (original) The semiconductor laser driving device of claim 1 wherein the first current generating unit, the second current generating unit, the third current generating unit, the auxiliary

Hiroaki KYOUGOKU et al., S.N. 10/531,755

Dkt. 2271/74286

Page 4

current generating unit, and the initialization unit are integrated on a single integrated circuit.

6. (original) A semiconductor laser driving device which performs a driving control of a semiconductor laser to control current supplied to the laser so that a desired amount of emission light is obtained, said semiconductor laser driving device comprising:

a first current generating unit generating a first current that is below an oscillation threshold current of the laser, and outputting the first current to the laser invariably;

a second current generating unit generating a second current that is needed for light emission of the laser responsive to an input signal, and outputting the second current to the laser;

a third current generating unit generating a third current that controls the laser such that a detected amount of emission light from the laser accords with a given value, and outputting the third current to the laser;

an auxiliary current generating unit outputting a predetermined auxiliary current to the laser in response to a control signal; and

an initialization unit performing an initialization operation to detect luminescence characteristics of the laser, and outputting a signal, indicating a value of the second current derived from the detected luminescence characteristics, to the second current generating unit,

wherein the third current generating unit controls the third current so that an amount of light outputted by the laser which receives a sum of the first current, the second current, the third current and the auxiliary current, accords with a predetermined amount.

7. (original) The semiconductor laser driving device of claim 6 wherein the auxiliary current generating unit generates the auxiliary current so that the generated auxiliary current is

Hiroaki KYOUGOKU et al., S.N. 10/531,755
Page 5

Dkt. 2271/74286

larger than a difference between a value of the second current derived from first luminescence characteristics of the laser detected at a normal temperature and a value of the second current derived from second luminescence characteristics of the laser detected at a predetermined high temperature when a same amount of light is outputted by the laser for the two temperatures.

8. (original) The semiconductor laser driving device of claim 6 wherein the auxiliary current generating unit outputs the auxiliary current indicating a current value according to a received signal, to the laser, and the initialization unit performs the initialization operation to detect not only first luminescence characteristics of the laser at a normal temperature but also second luminescence characteristics of the laser at a predetermined high temperature when a same amount of light is outputted by the laser for the two temperatures, and

wherein the initialization unit causes the auxiliary current generating unit to generate the auxiliary current so that the generated auxiliary current is larger than a difference between a value of the second current derived from the first luminescence characteristics and a value of the second current derived from the second luminescence characteristics.

9. (original) The semiconductor laser driving device of claim 6 wherein each of the second current generating unit and the auxiliary current generating unit comprises a current-output type DAC which generates a predetermined reference current and outputs a current based on the reference current according to a received digital signal.

10. (original) The semiconductor laser driving device of claim 6 wherein the first current generating unit, the second current generating unit, the third current generating unit, the

Hiroaki KYOUGOKU et al., S.N. 10/531,755

Dkt. 2271/74286

Page 6

auxiliary current generating unit, and the initialization unit are integrated on a single integrated circuit.

11. (original) The semiconductor laser driving device of claim 1 wherein, upon start of the initialization operation, the initialization unit causes the second current generating unit to stop outputting the second current and the auxiliary current to the laser, and causes the third current generating unit to output the third current to the laser so that the amount of light outputted by the laser is $1/N$ of the predetermined amount,

wherein the initialization unit causes the second current generating unit to output only the second current to the laser, detects the amount of light outputted by the laser, and causes the second current to be increased until the detected amount of light reaches the predetermined amount, and

wherein the initialization unit causes the third current generating unit to hold a value of the second current when the predetermined amount is reached, and causes the second current generating unit to output a new second current indicating $N/(N-1)$ of the held value of the second current, to the laser.

12. (original) The semiconductor laser driving device of claim 11 wherein the third current generating unit comprises:

a light amount detection unit detecting the amount of light outputted by the laser and outputting a voltage according to the detected amount of light;

a voltage-current conversion unit converting an input voltage into a current and outputting the current to the laser;

Hiroaki KYOUGOKU et al., S.N. 10/531,755

Dkt. 2271/74286

Page 7

a light amount control unit controlling the voltage inputted to the voltage-current conversion unit so that the output voltage of the light amount detection unit accords with a predetermined value, in order to control the amount of light outputted by the laser;

a first switch allowing outputting of the controlled voltage from the light amount control unit to the voltage-to-current conversion unit, in response to a received control signal;

a hold capacitor holding the controlled voltage outputted from the light amount control unit to the voltage-current conversion unit through the first switch; and

a control unit controlling switching operation of the first switch by sending the control signal to the first switch.

13. (original) The semiconductor laser driving device of claim 12 wherein, when a normal operation is performed immediately after the initialization operation, the initialization unit causes the discharging of the hold capacitor, and causes the control unit to activate the switching operation of the first switch so that the controlled voltage from the light amount control unit is outputted to the voltage-to-current conversion unit through the first switch.

14. (original) The semiconductor laser driving device of claim 12 wherein the light amount control unit comprises:

a reference voltage generating unit outputting a first reference voltage;

a voltage divider outputting a second reference voltage through a voltage division of the first reference voltage according to a received control signal; and

an operational amplifier outputting a voltage indicating a difference between the output voltage of the voltage divider and the first reference voltage,

Hiroaki KYOUGOKU et al., S.N. 10/531,755
Page 8

Dkt. 2271/74286

wherein the initialization unit controls the voltage division of the voltage divider when performing the initialization operation, so that the amount of light outputted by the laser is changed.

15. (original) A semiconductor laser driving method which performs a driving control of a semiconductor laser to control current supplied to the laser so that a desired amount of emission light is obtained, said method comprising the steps of:

generating a first current that is below an oscillation threshold current of the laser;

generating a second current that is needed for light emission of the laser responsive to an input signal;

generating a third current that controls the laser such that a detected amount of emission light from the laser accords with a given value;

performing an initialization operation to detect not only first luminescence characteristics of the laser at a normal temperature but also second luminescence characteristics of the laser at a predetermined high temperature when a same amount of light is outputted by the laser for the two temperatures; and

generating an auxiliary current so that the generated auxiliary current is larger than a difference between a value of the second current derived from the first luminescence characteristics and a value of the second current derived from the second luminescence characteristics;

wherein the third current is controlled so that an amount of light outputted by the laser which receives a sum of the first current, the second current, the third current and the auxiliary current, accords with a predetermined amount.

Hiroaki KYOUGOKU et al., S.N. 10/531,755
Page 9

Dkt. 2271/74286

16. (original) The method of claim 15 wherein, upon start of the initialization operation, outputting of the second current and the auxiliary current to the laser is stopped, and the third current is outputted to the laser so that the amount of light outputted by the laser is $1/N$ of the predetermined amount,

wherein only the second current is outputted to the laser, the amount of light outputted by the laser is detected, and the second current is increased until the detected amount of light reaches the predetermined amount, and

wherein a value of the second current when the predetermined amount is reached is held, and a new second current indicating $N/(N-1)$ of the held value of the second current is outputted to the laser.

17. (original) The method of claim 15 wherein the third current generating step comprises: detecting the amount of light outputted by the laser and outputting a voltage according to the detected amount of light;

converting an input voltage into a current and outputting the current to the laser;

controlling the input voltage so that the output voltage in the light amount detecting step accords with a predetermined value, in order to control the amount of light outputted by the laser;

allowing outputting of the controlled voltage in the light amount control step, in response to a received control signal; and holding the controlled voltage by a hold capacitor.

18. (original) The method of claim 17 wherein, when a normal operation is performed

Hiroaki KYOUGOKU et al., S.N. 10/531,755
Page 10

Dkt. 2271/74286

immediately after the initialization operation, discharging of the hold capacitor is caused, and the controlled voltage in the light amount control step is outputted.

19. (currently amended) An image forming apparatus including a semiconductor laser driving device which performs a driving control of a semiconductor laser to control current supplied to the laser so that a desired amount of emission light is obtained, said semiconductor laser driving device comprising:

a first current generating unit generating a first current that is below an oscillation threshold current of the laser, and outputting the first current to the laser invariably;

a second current generating unit generating a second current that is needed for light emission of the laser responsive to an input signal ~~and outputting the second current to the laser;~~

a third current generating unit generating a third current that controls the laser such that a detected amount of emission light from the laser accords with a given value, and outputting the third current to the laser;

an auxiliary current control unit causing the second current generating unit to generate a predetermined auxiliary current, the second current generating unit outputting a sum of the second current and ~~output~~ the auxiliary current to the laser; and

an initialization unit performing an initialization operation to detect luminescence characteristics of the laser, and outputting a signal, indicating a value of the second current derived from the detected luminescence characteristics, to the second current generating unit,

wherein the third current generating unit controls the third current so that an amount of light outputted by the laser which receives a sum of the first current, the second current, the third

Hiroaki KYOUGOKU et al., S.N. 10/531,755
Page 11

Dkt. 2271/74286

current and the auxiliary current, accords with a predetermined amount.

20. (original) An image forming apparatus including a semiconductor laser driving device which performs a driving control of a semiconductor laser to control current supplied to the laser so that a desired amount of emission light is obtained, said semiconductor laser driving device comprising:

- a first current generating unit generating a first current that is below an oscillation threshold current of the laser, and outputting the first current to the laser invariably;

- a second current generating unit generating a second current that is needed for light emission of the laser responsive to an input signal, and outputting the second current to the laser;

- a third current generating unit generating a third current that controls the laser such that a detected amount of emission light from the laser accords with a given value, and outputting the third current to the laser;

- an auxiliary current generating unit outputting a predetermined auxiliary current to the laser in response to a control signal; and

- an initialization unit performing an initialization operation to detect luminescence characteristics of the laser, and outputting a signal, indicating a value of the second current derived from the detected luminescence characteristics, to the second current generating unit,

wherein the third current generating unit controls the third current so that an amount of light outputted by the laser which receives a sum of the first current, the second current, the third current and the auxiliary current, accords with a predetermined amount.

21. (new) The semiconductor laser driving device of claim 1 wherein when the amount

Hiroaki KYOUGOKU et al., S.N. 10/531,755

Dkt. 2271/74286

Page 12

of light outputted by the laser based on the sum of the first current, the second current, the third current and the auxiliary current supplied to the laser is not in accord with said predetermined amount, the third current generating unit adjusts the third current so that the amount of light outputted by the laser is in accord with said predetermined amount.